

# BORNAS MONTAJE RÁPIDO SIN TORNILLO



## SERIES BCWK\*762\* . Paso 7.62 mm. (.300")

### Características

- Disponible de 2 a 24 circuitos
- Permite utilizar cable de 12 a 28 AWG
- Máxima corriente: 15 A máx. UL; 24 A máx. IEC
- Máximo voltaje: UL 300V, IEC 450V.
- Material aislante: PBT V-0
- Composición del terminal:
  - Contacto: bronce fosforoso 0.3 mm. de espesor
  - Retenedor del cable en latón estañado
- Pelado recomendado de 5 a 6 mm. (BCWK\*750A)
- Temperatura de trabajo: de -40° C a 130° C

Technical drawings showing dimensions for BCWKA762-XX-P. The top drawing shows a perspective view of the terminal block with dimensions: 13.00 (height), 14.25 (width), 0.70 (pitch), 1.50 (pitch), 2.15 (pitch), 7.62 (pitch), 0.70 (pitch), and 7.62xP+1.00 (total length). The bottom drawing shows a top view with dimensions: 7.62 (pitch), 5.00 (pitch), 3.65 (width), 6.05 (width), 15.00 (width), and 1.1-1.2 (hole diameter).

Código: **BCWKA762-XX-P**  
(XX=Nº contactos)

Technical drawings showing dimensions for BCWKA762A-XX-P. The top drawing shows a perspective view with dimensions: 7.62xP+1.0 (pitch), 14.20 (width), 6.60 (width), 1.50 (width), 3.1 (width), 7.62 (pitch), 10.80 (pitch), 5.40 (pitch), 5.00 (pitch), and 14.20 (width). The bottom drawing shows a top view with dimensions: 3.10 (pitch), 3.1 (pitch), 7.62 (pitch), 5.40 (pitch), 5.00 (pitch), 1.20-1.30 (hole diameter), and 14.20 (width).

Código: **BCWKA762A-XX-P**  
(XX=Nº contactos)

Technical drawings showing dimensions for BCWKV762A-XX-P. The top drawing shows a perspective view with dimensions: 7.62xP+1.0 (pitch), 14.0 (width), 2.90 (width), 3.15 (width), 7.62 (pitch), 7.75 (pitch), 5.35 (pitch), 5.00 (pitch), and 14.20 (width). The bottom drawing shows a top view with dimensions: 3.15 (pitch), 7.62 (pitch), 5.35 (pitch), 5.0 (pitch), 1.20 (pitch), 1.1-1.2 (hole diameter), and 14.00 (width).

Código: **BCWKV762A-XX-P**  
(XX=Nº contactos)

Technical drawings showing dimensions for BCWKR762A-XX-P. The top drawing shows a perspective view with dimensions: 7.62xP+1.0 (pitch), 14.20 (width), 6.60 (width), 13.60 (width), 3.1 (width), 7.62 (pitch), 10.80 (pitch), 5.40 (pitch), 5.00 (pitch), and 14.20 (width). The bottom drawing shows a top view with dimensions: 3.10 (pitch), 3.1 (pitch), 7.62 (pitch), 5.40 (pitch), 5.00 (pitch), 1.20-1.30 (hole diameter), and 14.20 (width).

Código: **BCWKR762A-XX-P**  
(XX=Nº contactos)

R