

20" Open Frame LCD R20T600-OFA1, R20T630-OFA1



Specification

Model Name	R20T600-OFA1, R20T630-OFA1
Viewable Size Image	20.1"
Active Display Area (mm)	408.0(H) x 306.0 (V)
Pixel Pitch (mm)	0.51(H) x 0.51(V)
Number of Pixels	800x600
Contrast Ratio	500:1
Display Color	16.7M (8 bits/colors)
Brightness (CD/m ²)	500
Viewing Angle (CR >=10)	-80~ 80 (H); -80 ~ 80 (V)
Synchronization Range	31.5-68Khz / 56-75Hz
Horizontal / Vertical	31.5-68Khz / 56-75Hz
Recommended Resolution	800x600 @60Hz,75Hz
Signal Connector	15 pin D-sub
Power Source	AC 100~240 V,Universal,±10%
Power Consumption	43 W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive, SAW

Remarks: R20T600 series = VGA input only
R20T630 series = VGA + Video input

* The specification is subject to change without notice. Manufacturer assumes no responsibility for Error Contained here in.