

## IP65 Solution



15"

### Specifications

**RoHS**  
COMPLIANT  
2002/95/EC

Model Name	T15600L-IP03
Viewable Size Image	15"
Active Display Area(mm)	304.1(H)x228.1(V)
Pixel Pitch(mm)	0.297(H)x0.297(V)
Number of Pixels	1024x768
Contrast Ratio	700:1(typ.)
Display Color	16.2M(6bit+FRC)
Brightness(cd/m <sup>2</sup> )	250(typ.)
Viewing Angle(CR>=10)	-70~70(H);-65~60(V)(typ.)
Synchronization Range	
Horizontal/Vertical	31.5~60.0KHz/60~75Hz
Recommended Resolution	1024x768@60Hz, 75Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	25W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive, SAW*, IR

Remarks: T15600L series= VGAinput only

T15630L series= VGA+Video InputT

\*When adding SAW touch, the IP grade will be IP54

### Mechanical Drawing

